

AS25

DUST AND ASBESTOS CONTROL

Fibre binder for fixing dust and asbestos fibres



AS25 is used for fixing dust and asbestos on surfaces before removing e.g. roofing sheets, insulation materials, plaster and paint.



AS25 product information



- **Fibre binder for fixing dust and asbestos fibres**
- **Can be used both indoors and outdoors**
- **The product is water-based and VOC-free**
- **High surface penetration**
- **Dries completely within a few days.**


Area of application

Protox AS25 fixes dust and asbestos fibres on all surfaces both indoors and outdoors before removal/demolition, such as roofing sheets, insulation materials, plaster, paint and similar coatings and materials to reduce the risk of dust and fibre formation and spread.

To be used by professionals only.



Technical information

Product description	For professional use only
<p>AS25 fixes dust and asbestos fibres on all surfaces both indoors and outdoors before they are removed/demolished, such as roofing sheets, insulation materials, plaster, paint and similar coatings and materials to reduce the risk of dust and fibre formation and spread.</p> <p>AS25 has a low content of preservative that protects the product from rotting and mould growth and can therefore have a limited preventive effect on the treated surfaces.</p> <p>The product forms a diffusion-open film that encapsulates dust and fibres. The film does not stick after drying. The product has added UV marker and can be added green marker colour.</p>	
How to use	Occupational health and safety
<p>AS25 can be used indoors and outdoors, on asbestos-containing surfaces such as roofing sheets, insulation materials, plaster, paint and the like before they are removed.</p> <p>The product is applied with a low pressure sprayer (<10 bar), roller or brush until the surface is saturated.</p> <p>ATTENTION! Only apply to dry surfaces. Shake the product before use. Do not dilute the product.</p>	<p>IMPORTANT: "The product does not replace the use of protective equipment or subsequent cleaning".</p> <p>Follow the Danish Working Environment Authority's guidelines on asbestos work, including the section on cleaning and inspection before completing asbestos work.</p>
Product data	GHS classification
<p>Packaging: 10 litre jerry-can</p> <p>Dilution: AS 25 is ready to use and must not be diluted.</p> <p>Coverage: Up to 12 m² per litre depending on surface porosity</p> <p>Application temperature: 5-35 °C.</p> <p>Drying time: 1 to 12 hours depending on usage, humidity and temperature</p> <p>pH: 7-8</p> <p>Odour: Faint characteristic</p> <p>Cleaning: Clean the equipment used with soap and water</p> <p>Storage: Store at 5 to 20 °C.</p> <p>Shelf life: 12 months from production date. See labelling on the packaging</p> <p>Disposal: Dispose of empty packaging as hard plastic.</p> <p>PROTOX ApS, Fabriksvej 19, 6000 Kolding, Denmark Phone +45 75 50 40 22, info@protox.dk, protox.dk</p>	<p>Safety information</p> <p>"Always follow the information on the product label." Always read the safety data sheet before use.</p>