PROTOX
Professional Protection Process

SC20

FIRE DAMAGE REMEDIATION

Low-alkaline detergent

SC20 is a low alkaline agent for removing soot, oil, grease and other types of ingrained dirt. The product is especially suitable for post-fire cleaning.

SC20 product information

- **Low-alkaline cleaner for fire damage remediation**
- **Effectively dissolves and removes soot, oil, grease and other dirt**
- **Based on VOC-free ingredients**
- **Particularly effective for cleaning hard surfaces such as metal and plastic, ceramics and most painted surfaces**
- **Can be used for cleaning delicate surfaces such as upholstered furniture, carpets and clothing.**

Application area

SC20 is a low-alkaline cleaner for thorough cleaning and removal of soot, oil, grease and other types of ingrained dirt after fire. The product can be used for cleaning items with delicate surfaces damaged by fire, such as upholstered furniture, carpets and clothing. Can be used by both professionals and consumers.

SOLUTIONS FOR PROFESSIONAL BUILDING REMEDIATION SINCE 2003

© PROTOX

SC20

PROTOX

Technical information

Product description

SC20 is a low-alkaline cleaner for thorough cleaning and removal of soot, oil, grease and other types of ingrained dirt after fire. The product can be used for cleaning items with delicate surfaces damaged by fire, such as upholstered furniture, carpets and clothing.

Can be used by both professionals and consumers.

The product is a concentrate that must be diluted according to the use situation.

Before and after use

How to use

SC20 can be applied by spray, brush, sponge or cloth. Leave the product on for about 5 minutes, then work the surface thoroughly and rinse with water. The optimal water temperature is 20-50°C, but the product can also be used in cold water.

The product can be applied with a pressure washer or foam application equipment. Apply a thick layer to the surfaces, starting from the bottom and working upwards. Leave the solution to work for about 15 min. and rinse with water.

It may be necessary to treat heavily soiled areas with a brush or scouring pad.

Occupational health and safety

As any contact with cleaning products in general poses a risk of skin dehydration and irritation or permanent damage to the eyes, always work with the necessary protective equipment, including gloves and face shields/goggles.

See the safety data sheet for detailed information. The product does not contain any volatile substances, including perfumes and fragrances. Based on the ingredients used, the product is assessed to be indoor air neutral.

Product data

Dosage depending on the nature of the job:
Fire damage restoration: 5-10% in water
Foam application: 2-5% in water
High pressure cleaning: 2-5% in water
Heavy duty cleaning: 2-5% in water
All-purpose cleaning: 1-2% in water

Packaging: 5.0 litre jerry-can
Application temperature: 0-50° C, can also be used in cold water.
pH: Approx. 9.9
Smell: Characteristic
Cleaning: Rinse utensils and equipment thoroughly with water
Storage: SC 20 should be stored frost-free and protected from direct sunlight
Shelf life: If stored correctly, 2 years from date of production

PROTOX ApS, Fabriksvej 19, 6000 Kolding, Denmark
Phone +45 75 50 40 22, info@protox.dk, protox.dk

GHS classification

Warning
Causes serious eye irritation.

Safety information
"Always follow the information on the product label."
Always read the safety data sheet before use.
Available at protox.dk.

© PROTOX